

Electric Screwdrivers equipped with a mechanical shut-off-clutch

Ideal for basic applications in environments without compressed air

- economical
- air independent

The cost-effective electric screwdriver with mechanical shut-off clutch is a good alternative if no pneumatic connection is available. Our range of handheld electric screwdrivers provides the customer with the familiar quality features of DEPRAG screwdriving systems. This ergonomic screwdriver is available with varying functions such as e.g. push-to-start or lever start. For all screwdriver types speed regulation is possible. Seven performance classes cover the application areas for precision engineering screw assemblies up to M6 or 12 Nm. The torque set on the mechanical shut-off clutch has an accuracy of $\pm 3\%$ standard deviation. The separate electricity supply of 32 V and 40 V extra-low voltage ensures safe usage.

Our standard program for inserting tools is applicable.



ADVANTAGES

Drive

The screwdriver is equipped with a brushless drive motor with low voltage supply. The high degree of efficiency of the EC motor results in a larger torque and speed range in a lower weight and smaller diameter screwdriver.

Power range

Throughout the four sizes, shut-off torque can be set from 0.04 to 12 Nm. The high speeds of up to 1000 rpm guarantee short screw cycle times.

ESD capability

All screwdrivers fulfil the requirements for the processing of ESD-sensitive components.

Precision

Under suitable processing conditions Cmk-values of >1.67 are reached with a tolerance of ±10%.

Electricity supply

The power units have a wide range of input voltages and can be used worldwide in connection with country-specific power cables.

TECHNICAL DATA

Electric Screwdrivers, handheld, straight

Screwdriver reversible Lever-Start	Type Part no.	342EGT-0003 454500A	342EGT-0012 454501A	342EGT-0019 454502A	342EGT-0029 454503A	342EGT-0049 454504A	342EGT-0088 454505A	342EGT-0120 454512A
Screwdriver reversible Push-to-Start	Type Part no.	- -	342EGA-0012 454506A *)	342EGA-0019 454507A *)	342EGA-0029 454508A *)	342EGA-0049 454509A *)	342EGA-0088 454510A	342EGA-0120 454511A
Screws	up to	M2	M3	M4	M4	M5	M6	M6
Torque min.	Nm / in.lbs	0.04 / 0.4	0.15 / 1.3	0.3 / 2.6	1 / 8.85	2 / 17.7	3 / 26.5	4 / 35.4
Torque max.	Nm / in.lbs	0.3 / 2.6	1.2 / 10.6	1.9 / 16.8	2.9 / 25.7	4.9 / 43.4	8.8 / 77.9	12 / 106.2
Speed – reversible	rpm	700/1000	700/1000	700/1000	750/1000	750/1000	600/800	400/550
Handle – diameter	mm / in.	30 / 1.2	36 / 1.4	36 / 1.4	40 / 1.6	40 / 1.6	46 / 1.8	46.5 / 1.81
Length	mm / in.	210 / 8.2	238 / 9.3	238 / 9.3	277 / 10.8	277 / 10.8	310 / 12	310 / 12
Weight	kg / lbs	0.39 / 0.86	0.52 / 1.14	0.52 / 1.14	0.8 / 1.76	0.8 / 1.76	1.2 / 2.64	1.2 / 2.64
Noise level	dB (A)	66	68	68	68	68	68	68
Line voltage	V	32	32	32	40	40	40	40
Quick change chuck Hex female DIN ISO 1173		F6.3	F6.3	F6.3	F6.3	F6.3	F6.3	F6.3

Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 – E6.3 (1/4"), see also our brochure D3320E.

*) Also available in combination with feeder.

Required Accessories

Screwdriver cable (2m)	Type Part no.	included in delivery	KS2-2m 833782	KS2-2m 833782	KS3-2m 833783	KS3-2m 833783	KS3-2m 833783	KS3-2m 833783
Power unit	Type Part no.	NG32 833770	NG32 833770	NG32 833770	NG40 834500	NG40 834500	NG40 834500	NG40 834500
Source (AC)	V/Hz	110-240/50-60	110-240/50-60	110-240/50-60	100-240/50-60	100-240/50-60	100-240/50-60	100-240/50-60
Output (DC)	V	32	32	32	40	40	40	40
Dimensions L x W x H	mm	150x48x130	150x48x130	150x48x130	210x135x70	210x135x70	210x135x70	210x135x70
	in.	5.85x1.87x5.07	5.85x1.87x5.07	5.85x1.87x5.07	8.19x5.26x2.73	8.19x5.26x2.73	8.19x5.26x2.73	8.19x5.26x2.73
Weight	kg / lbs	0.95 / 2.09	0.95 / 2.09	0.95 / 2.09	1.8 / 3.96	1.8 / 3.96	1.8 / 3.96	1.8 / 3.96
Power cable EU	Type Part no.	KN-C5/EU 833787 (1.5m)	KN-C5/EU 833787 (1.5m)	KN-C5/EU 833787 (1.5m)	KN-C13/EU 833790 (2m)	KN-C13/EU 833790 (2m)	KN-C13/EU 833790 (2m)	KN-C13/EU 833790 (2m)
alternative:								
Power cable US	Type Part no.	KN-C5/US 833788 (1.5m)	KN-C5/US 833788 (1.5m)	KN-C5/US 833788 (1.5m)	KN-C13/US 833791 (2m)	KN-C13/US 833791 (2m)	KN-C13/US 833791 (2m)	KN-C13/US 833791 (2m)
Power cable UK	Type Part no.	KN-C5/UK 833789 (1.5m)	KN-C5/UK 833789 (1.5m)	KN-C5/UK 833789 (1.5m)	KN-C13/UK 833792 (2m)	KN-C13/UK 833792 (2m)	KN-C13/UK 833792 (2m)	KN-C13/UK 833792 (2m)
Power cable Brazil	Type Part no.	KN-C5/BR 105624 (1.8m)	KN-C5/BR 105624 (1.8m)	KN-C5/BR 105624 (1.8m)	KN-C13/BR 207388 (1.8m)	KN-C13/BR 207388 (1.8m)	KN-C13/BR 207388 (1.8m)	KN-C13/BR 207388 (1.8m)
Power cable China	Type Part no.	KN-C5/CN 105622 (1.8m)	KN-C5/CN 105622 (1.8m)	KN-C5/CN 105622 (1.8m)	KN-C13/CN 832927(2m)	KN-C13/CN 832927(2m)	KN-C13/CN 832927(2m)	KN-C13/CN 832927(2m)

OPTIONAL EQUIPMENT

Suitable for Type		342EGT-0003	342EGT-0012	342EGT-0019	342EGT-0029	342EGT-0049	342EGT-0088	342EGT-0120
		-	342EGA-0012	342EGA-0019	342EGA-0029	342EGA-0049	342EGA-0088	342EGA-0120
Pistol grip (for use as pistol grip screwdriver)	Type	-	PG2-EGT	PG2EGT	PG3-EGT	PG3-EGT	-	-
	Part no.	-	816054	816054	8337941	8337941	-	-
	Type	-	PG2-EGA	PG2-EGA	PG3-EGA	PG3-EGA	-	-
	Part no.	-	816053	816053	833794	833794	-	-
Screwdriver adaptor (for torque support with linear stand or parallelogram stand)	Part no.	4008330E	4008330B	4008330B	4008330C	4008330C	4008330D	4008330D
Handle	Type	-	-	-	-	-	HG4-EGA/EGT	HG4-EGA/EGT
	Part no.	-	-	-	-	-	8337942	8337942
Slow-Start Module without process monitoring (connection between power unit and screwdriver)	Type	SL	SL	SL	SL	SL	SL	SL
	Part no.	103305	103305	103305	103305	103305	103305	103305
Slow-Start Module with process monitoring (connection between power unit and screwdriver)	Type	PK	PK	PK	PK	PK	PK	PK
	Part no.	816699	816699	816699	816699	816699	816699	816699
Protective sleeve - metal design (as an alternative to the plastic adjustable protection included in delivery)	Type	HS1-1	HS2-1	HS2-1	HS3-1	HS3-1	-	-
	Part no.	421322	419336	419336	419447	419447	-	-
Torque setting tool (to set the torque without disassembling the protective sleeve)	Type	WK1	WK2	WK2	WK3	WK3	-	-
	Part no.	834133	834134	834134	834135	834135	-	-
Screwdriver cable, additional options:								
Straight cable, length 3 m / 9.8 ft.	Part no.	-	834034	834034	834034	834034	834034	834034
Spiral cable, length 2 m / 6.6 ft.	Part no.	-	834036	834036	834036	834036	834036	834036
Vacuum connector	Part no.	104750A	418477A	418477A	418446A	418446A	-	-

 <p>Power unit NG32</p> <p>Power unit NG40</p>	 <p>Screwdriver adaptor for torque support with linear stand or parallelogram stand.</p>	<p>Slow-Start Module</p> <ul style="list-style-type: none"> → enables a screwdriving step with low speed before screwdriving to torque → soft start to ensure proper bit engagement → duration and speed of the steps can be adjusted → signals for „direction of rotation“, “shut-off” and “external start release” → the module type PK can be used in conjunction with a PLC to control the process 
<p>With pistol grip PG2-/3-.. the electric screwdriver (straight version) can also be used as pistol grip screwdriver.</p> 	 <p>Handle Type HG4-EGA/EGT can be optionally used with screwdriver type 342EGT/EGA-0088.</p>	<p>Torque setting tool</p> <ul style="list-style-type: none"> → for torque setting without disassembly of the protective sleeve → when frequent changes of the shut-off torque are necessary. 

Remark:

Details on our feeding systems can be found in brochure D3820E.

DEPRAG

DEPRAG SCHULZ GMBH u. CO.

P.O. Box 1352, D-92203 Amberg, Germany
Carl-Schulz-Platz 1, D-92224 Amberg
Phone (+49) 9621 371-0, Fax (+49) 9621 371-120
www.deprag.com
info@deprag.de



CERTIFIED AS PER DIN EN ISO 9001
